

SHANTOU HIGH TECH ZONE JUSHENG TECHNOLOGY CO.LTD

CODE: 204

80g ART PAPER/HOT MELT ADHESIVE B-02/WHITE GLASSINE





Application

- Minimum labeling temp: 10°C Service temp: -15°C~90°C.(24h after labeling)
- Suitable for Food or Medicine label in conventional gloss.
- Must test to confirm if used in small bottle label (diameter smaller than 30mm).

Print & Process

- Suitable for conventional printing.
- Full page printing is not recommend.

Facestock

Art paper, glossiness between matte & high gloss.

Indicator	Parameter	Unit	Method
Substance	$80 \pm 5\%$	g/m^2	ISO 537
Caliper	$70 \pm 5\%$	μш	ISO 534

Adhesive

General purpose permanent hot melt adhesive

Liner

Super calendered white glassine

Indicator	Parameter	Unit	Method
Substance	$60 \pm 5\%$	g/m^2	ISO 537
Caliper	$53 \pm 5\%$	μш	ISO 534
Tear Resistance	≥300	mN	ISO 1924

Performance data

Indicator	Parameter	Unit	Method
Initial Tack	≥17 or PT	N/25mm	FTM9, ss
90° Peel Adhesion (20min)	≥9 or PT	N/25mm	FTM2, ss

Shelf life

From date of manufacture:12 months, storage conditions: $23\pm2^{\circ}$ C & relative humidity $50\pm5\%$. Prolonged storage outside these conditions might reduce the shelf life.

Statement:

- All the statements, tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
- We reserve the rights of finally explanation.